

# Middle Point R/C Flyers



## December 2017 Newsletter

### Upcoming Events:

January 4 – Membership Meeting

February 1 – Membership Meeting

March 1 – Membership Meeting

March 17 – MPRCF Swap Meet

April 5 – Membership Meeting

May 3 – Membership Meeting

June 7 – Membership Meeting

July 5 – Membership Meeting

August 2 – Membership Meeting

August 24-25 – MTRCCA Fall Fly-In  
– Dickson Airport

September 6 – Membership Meeting

October 4 – Membership Meeting

November 1 – Membership Meeting

November 3 – MTRCCA Swap Meet  
– Antioch, TN

December 7 – Membership Meeting

January 3, 2019 – Membership Meeting

### Prez Says

As I write this it is nearly 2018. I hope that everyone has a Happy New Year. 2017 was a good year for the club and I expect that 2018 will be even better.

The development of the new field was a big undertaking and I think that it turned out great. We still have some improvements to make but we've made a terrific start. I want to thank all of the club members who dedicated their time and resources toward the field's development. Without these volunteers things don't get done.

I encourage all members to view our club as if you are an owner and not simply a guest. As an owner, you have a vested interest in, and an incentive to, improve the club in all areas. There are a lot of improvements needing to be done and I need volunteers to step up to help get them done. Please review the Meeting Minutes in this Newsletter and

**Continued**

<https://www.facebook.com/groups/mprcf/>

[www.mprcf.com](http://www.mprcf.com)

## December Meeting Minutes:

The meeting, held at O'Charley's, was called to order by Dan Wandell @ 6:05pm. There were 12 members present. There was 1 guest.

The November meeting minutes were accepted as published in the Newsletter.

The November Treasurer's report was read and accepted.

There were 5 new members added since the last meeting.

Old Business:

### Upcoming local events:

- Indoor Flying – Smyrna, TN – every Tuesday – contact Family Hobbies for info.

### Association Swap Meet:

The Association's Swap Meet was a good event. The Association netted about \$1,500 which will be included in the year-end distribution to the member clubs. MPRCF did more than its share of the organizing and running of the event. In the future, a better distribution of the workload between the clubs will be done. Those members who volunteered to help with the event were thanked.

**Continued**

## Prez Says (cont.):

consider volunteering to lead one of the areas that are currently leaderless. Leading the effort doesn't mean that you do it all the work, it means that you coordinate getting it done.


Speaking of volunteers, Jessica Waggener has graciously volunteered to be the club's Newsletter Editor starting in January. Thanks Jessica!! Members are encouraged to submit items for possible inclusion in the newsletter to Jessica or me. Pictures, articles, etc. are welcome.

I'm looking forward to the 2018 flying season. Now that we have a club field I hope to see us hold some events during the year. Hosting events has always been a lot of fun and it is also a good way for the club to raise money for club operations or for charity. If you have an idea for an event let our Event Coordinator, Richard Ricca, or me, know.

For those who may not know, Family Hobbies sponsors indoor flying during the winter months. Every Tuesday (except 1/2/18) through the end of February, from 6:30 to 9:30pm, there is indoor flying at the Highlands Heights Church in Smyrna. See the flyer later in the Newsletter for more information.

Voting for the 2018 officers took place at the December membership meeting. As expected, all nominees were unanimously elected. 😊 I want to thank Don Perry and Greg Doe, who both retired from office, for their help this past year and I welcome John Dudinetz and Richard Ricca as our newest officers.

**Continued**



# December Meeting Minutes (cont.):

## Field Development:

### Since November Meeting:

- Removed some trees from the north end
- Installed drain pipe at the field gate
- Established an address for emergency responders – 1004 Central Valley Road, Murfreesboro, TN 37129
- Fence line at the entrance has been removed by the city

### Pending Actions:

- Remove trees at north approach
- Remove stumps in runway at the north end
- Remove rocks and other debris in the east runway perimeter
- Add “X” to runway ends
- Install giant scale starting stations
- Install sign with field’s address and emergency responder phone numbers
- Seed in the spring

## Field Maintenance Items:

- Fix drainage at the entrance gate
- Evaluate/repair starting stations
- Clean tables/chairs/bleachers
- Shore up field gate which is sagging
- Relocate pilot stations
- Install first aid box

## Airplane Setup for Gerry Rollins:

Purchased an e-Flite 1.2m BNF T-28 from Family Hobbies. \$120 of budget remains for batteries and a charger. No action since last meeting.

## Storage Container:

Need to install a ramp; John Dudinetz volunteered to help coordinate. Need to install a locking dividing wall (maybe roll-up door?) and install vents for cooling and for battery venting. No action since last meeting.

## Charging Station:

We have batteries. The remaining equipment needs to be purchased and installed. John Dudinetz volunteered to help coordinate. No action since the last meeting.

**Continued**

## Dec. Meeting Minutes (cont.):

### Garage Ports:

Inquiries were made with several suppliers: Watson's Portable Buildings, MetalMax Steel Buildings, and Horizon Steel Structures. Further evaluation will need to be made to determine size, number of units, and placement prior to purchase. No action since last meeting.

### Club Orientation Airplane:

We remain on the lookout for an airplane to be used as an orientation airplane for introductory flights for potential members and spectators. Securing an introductory drone might have value too. Any aircraft acquired for this purpose would not be used for flight instruction.

### TN Veteran's Home Presentation/Field Visit:

The TN Veteran's Home, located in Murfreesboro near the VA, asked if the club could make a presentation to their residents and allow them to visit the field sometime. Dick Tonan and Richard Ricca volunteered to coordinate this effort. No action since last meeting.

### 2018 Events:

Members are asked to offer suggestions for events that they would like to see held at the field. We plan to host an Open House sometime during the spring. We will host a Model Aviation Day event (jointly with Cane Ridge) in August.

**Continued**



**Next  
Club Meeting!  
January 4, 2018**

## Prez Says (cont.):

If you're looking for something different to do over winter, stop by the Tennessee Valley Model Railroad Club located in Smyrna behind the Shoney's Restaurant. They are open for visitors every Saturday from 10:00 to 4:00pm. They have quite a setup with "miles" of scale track going through some pretty cool dioramas. For info check out their website: <http://tennesseevalleymodelrailroadclub.org/main.html>

In case you are not aware, the FAA requirement to register UAVs over .55lbs has been reinstated. Per the AMA: "On December 12, 2017, President Trump signed legislation that will reverse the earlier court ruling in the John Taylor case and restore the FAA's UAS registration requirement, including for AMA members." For more information see the AMA's website: <http://www.modelaircraft.org/aboutama/faa-uas-faq.aspx>.

Take care to register directly with the FAA's website: <https://registermyuas.faa.gov/>. There are many websites that will help you register but they come with a fee that is unnecessary since the registration process is very easy.

Consistent with the AMA's position, MPRCF encourages compliance but we will not police compliance – that remains the responsibility of each individual member.

Well...that's it for this month.

Happy New Year!!

Dan



## December Meeting Minutes (cont.):

Consideration may be given to hosting the Association's Spring Fellowship Fly-In in June.

### 2018 Officer Election:

The following were unanimously elected:

- President-Dan Wandell
- Vice-President-Dick Tonan
- Treasurer-John Hagel
- Safety Coordinator-Jim Powers
- Event Coordinator-Richard Ricca
- Field Maintenance Director-John Dudinetz

### New Business:

#### 2018 Association distribution:

We expect to receive about \$660 from the Association for the 2018 net proceeds from the Association's three events.

#### Newsletter Editor:

We need a Newsletter Editor. The Editor received free dues the following year they serve. No one has volunteered so the search will continue. Without a volunteer the Newsletter may stop being published.

#### Swap Meet:

The Swap Meet will be held on March 17. We need to formalize the contract with the armory.

#### 2018 Dues:

The 2018 dues were discussed and it was decided to maintain the same dues amounts for 2018. Members were reminded that dues paid after March 1 will be subject to a \$15 reinstatement fee so everyone is encouraged to renew before then. Reminder emails will be sent out.

#### January Meeting Location:

The January meeting will be held at O'Charley's.

Meeting adjourned at 7:19pm.

## Look who made the AMA Magazine!

### **District V**—Alabama, Florida Tennessee, US Virgin Islands




**Bob Brogdon**  
*Vice President*

r.a.brogdon@comcast.net  
5251 Hermitage Dr., Powder Springs GA 30127  
Tel.: (770) 421-8838; [www.amadistrict-v.org](http://www.amadistrict-v.org)

**Hello District V** and friends! Thanks for joining me this month. I appreciate the feedback I have received and the interest you have shown in my column. I hope I can continue to keep your attention.

I am pleased to report that we have two new Leader Members: Robert G. Miller Sr. of Athens, Tennessee, and Daniel Wendell of Murfreesboro, Tennessee. Thank you Robert and Daniel!

We also have four new Contest Directors/Event Managers: James Ogorek of Tallahassee, Florida; Alan Tahler of Rossville, Georgia; Richard Bobb of Sarasota, Florida; and Edward Dumas of Knoxville, Tennessee. Thanks, guys!



# Photos From the Field – December 2017









# Need a place to fly this Winter indoors??

Come Join "Family Flyers"

Tuesday nights

6:30pm – 9:30pm

Highland Heights Church

785 S. Lowry St., Smyrna, TN 37167

*(located in the Gym behind the church)*

Cost one time fee of \$20 to fly November 7th thru Feb 27<sup>th</sup>

You must have an AMA Membership

*(AMA is free to youth under 19 years of age)*

Max 36" wing span on planes and micro Heli's/Quad's

See one of our staff for options in the store under \$100

with battery and transmitter! Great Christmas Gift!



**FAMILY**  
**HOBBIES**  
"Where Families Bring Fun To Life!"

615-355-0775

# Radio Programming Basics

## Model Aviation

The Online Flagship Publication for the Academy of Model Aeronautics

Published on *Model Aviation* (<http://www.modelaviation.com>)

[Home](#) > Radio Programming Basics

---

## Radio Programming Basics



*Written by Tony Stillman*

*Understanding and utilizing basic features of your RC transmitter*

*Technical*

*Bonus digital content in the July 2017 issue of Model Aviation.*

Today's model fliers have many great choices for radio equipment. Most are multi-model capable, allowing a single transmitter to control multiple aircraft by creating a program profile of each specific model, and then saving it to the radio's memory to be recalled whenever you want to fly that aircraft again.

This article will try to help new modelers better understand the features available in most RC transmitters today. Knowing how the features affect the model's flying characteristics can transform a hard-to-fly model into an easy flying, enjoyable aircraft. Let's get started!

### **Transmitter Features:**

#### **Mode Types**

It is important to understand how the transmitter is set up. The stick mode (Mode 1 or Mode 2) refers to the stick configuration of an aircraft transmitter's control sticks. Mode 2 is the USA standard and has the elevator/aileron on the right stick and the rudder/throttle on the left. It is most likely what you are using.

## **Servo Reversing**

This feature allows you to reverse a specific channel's servo rotation. If the servo on a specific channel moves in the opposite of its intended direction, this feature corrects the problem.

## **Sub-Trim**

Sub-trim allows you to fine-tune the neutral position of the servo arm on a particular channel.

## **End-Point Adjustment**

Also called adjustable travel volume (ATV) in some systems, this allows you to preset the maximum travel of a servo on either side from its neutral position, or the high or low side of a throttle channel. This allows you to make changes to match the throw settings that are recommended for the aircraft.

## **Dual Rates**

A dual-rate switch on the transmitter can reduce the amount of servo travel. The aileron and elevator control channels are the most common channels used with this feature, although some radios will also have a rudder dual-rate switch. Select low rates, and an overresponsive model can be made easier to control.

## **Exponential**

This feature adjusts how linear the relationship is between the transmitter stick and the response of the servo. This is normally used to reduce the servo response near the neutral or center of the stick, and increase it as the stick is moved toward the maximum travel. The effect on the model is to give it lots of control movement (like a 3-D model) and still fly like a trainer.

## **Mixing**

Two control channels can be mixed or coupled together so that they move together when only one control channel is activated. Many scale models require a combination of aileron and rudder to turn. Mixing does this electronically at the transmitter.

## **Failsafe**

This feature automatically returns a servo or servos to a neutral or a preset position in case of a malfunction or interference.

## **Programming a Model**

Now, let's now go into more detail on each of these features to better understand them. I put these features in this specific order because this is the order you should use them in setting up a new model.

Get your transmitter and your airplane fuselage with all of the radio gear installed, in front of yourself and follow along using your radio and airplane instruction manuals.

This exercise will help you see the results of the features one by one, and how they can make your model flying a more enjoyable experience.

We want to program this aircraft from the beginning. Referring to your radio manual, access the model menu and select a new model, or reset the programming of the model you want to use. Name the model and then turn off the receiver and transmitter.

Now that all of that is saved to memory, turn everything back on. Because we have the wing off of the model to view the servos, we will only focus on the elevator, rudder, and throttle channels on this particular airplane.

## **Elevator**

First, verify that the servo you want to be controlling the elevator is following the motion of the elevator stick on your transmitter. If the elevator is working when the rudder stick is moved, for example, you need to swap the connection of that servo to the correct channel. Check each function to make sure you have this correct for all servos. If you find something wrong, swap the servo connectors to the correct channel of the receiver until all of them respond properly.

Next, we need to see if the servos are moving in the correct direction as we move the sticks. Connect the elevator pushrod to the servo arm. If you find that the elevator servo is moving in the wrong direction when you pull back on the elevator stick, then you can simply move the pushrod to connect to the other side of the servo arm or wheel.

If you don't have space or can't move the pushrod, then the elevator channel needs to be reversed. Check with your manual, access the servo reversing program, and then select the elevator channel. Change the setting from normal to reverse to change the direction. Now your servo should be moving in the opposite direction when you pull back on the stick, resulting in up-elevator motion. Simple and easy!

Check the rest of the channels and make changes as needed in the servo-reversing program so that everything is moving in the correct direction. If you have an electric-powered model, you will need to follow the instructions for the ESC to verify that the throttle stick direction is correct. Make sure that you do this with the propeller removed from the motor!

## **Sub-Trim**

Now that we have all of the controls working in the proper direction, let's move to the next step: sub-trim. Make sure that all of the sticks and trims are in the neutral position. You can verify the trims using the display and listening for the tone change when the trim is centered.

With that task completed, take a close look at the relationship of the servo arm and the pushrod attached to it. For 99% of all setups, you want the pushrod to connect to the servo arm and create a 90° angle. You can unscrew the servo arm screw, pull off the arm, and reposition it to get it as close as possible. This ensures that the servo's motion will have the same effect (deflection angle) on the control surface as you go from one side of neutral to the other.

In the case of elevator control, if you move the stick 1 inch to either side of neutral, you should get the same angle change on the control surface. This will make the aircraft responsiveness symmetrical throughout total travel. This basic starting point is required to get the most out of future adjustments.

If you find that the servo arm is not perfectly at 90° to the servo and pushrod, then you need to go into your sub-trim menu and adjust the channel. You will find that this is a very fine adjustment, and you can be extremely accurate.

Go through the rest of the controls to make sure they are the same. In the case of glow or gas-powered models, make sure the carburetor arm is also at 90° to the pushrod when at neutral stick or half throttle. You might even need to make an adjustment to the carburetor arm position to achieve this. Check with your engine instructions for how to do this.

Now that the servos are working in the proper direction and fine-tuned to exact center, we want to adjust the total travel of the servo to get the correct amount of travel at the flight controls.

Review the travel amounts that are listed in the instructions that came with the aircraft. If you don't have instructions, then you have to use your best guess, or ask another modeler who has the same or a similar airplane, for recommendations on control surface throw.

After you decide on the amount, it's time to do some measuring. There are several tools out there that you can purchase to check control throw and they all have advantages, but for now, we are going to use an old-fashioned method: a ruler. Let's use the elevator surface for our example.

With the radio turned on and everything centered, check the elevator position to be sure it is exactly neutral. If not, adjust the clevis in or out until it is in neutral. Get your ruler and align the elevator's trailing edge on an inch or millimeter mark so you can measure how far the control will move with stick movement. Move the elevator stick on the transmitter to full up-elevator and measure how far the control surface moved. Check this against the recommended throws.

If the travel is too much, try moving the pushrod connection to the next hole outward on the control horn on the elevator. You can also move the pushrod connection at the servo horn in toward the center of the servo arm. Either one or both of these adjustments can be done to get close to the desired amount of throw.

To increase the throw, move the pushrod connection in the opposite direction. You want to be roughly the same distance from the center of the servo to the pushrod as you are from the hinge line of the elevator to the pushrod connection. By trying different positions, you will find a location that gives you nearly the desired travel on the elevator.

## Endpoint Adjustment

Now that you are close, you can use the endpoint adjustment feature to adjust the travel to the exact specifications. Most radios will typically default to 100% travel in both the up and down side of each channel, which can be individually adjusted. You might think that this is maximum available travel, but most are adjustable up to 125% and some even up to 150%. This allows you to increase above 100% to get the travel properly adjusted.

Keep in mind that you want to keep the endpoint adjustment between 75% and 120% in order to have the best resolution for the servos. If you need more or less throw than these numbers, go back and change the pushrod connection point on the servo arm or control horn as needed, and repeat the process.

Following the radio instructions, access the endpoint adjustment program and select the elevator channel. Move the transmitter stick to give full up-elevator and measure the travel. If you need more travel, increase the percentage. If you need less, decrease it.

Do this for both the up and down side of the elevator, and once it is completed, recheck it. When you are happy with the setting, move to the rudder and throttle. For glow or gas engines, you want the full-throttle setting to fully open the carburetor, but not stall the servo.

Listen for a buzzing sound from the servo that would indicate that you have gone past the stop for the carburetor and the servo is no longer moving. Reduce the travel until the buzzing stops and make sure the carburetor barrel is fully open at full throttle.

For low throttle or idle, you want to move the stick to low throttle and completely close off the opening in the throttle barrel using the sub-trim. Now open it back up to show approximately 1/16 inch of opening. This should be a starting point for idle that can be finely adjusted using the trim lever next to the stick when you run the engine. For electric motors, follow the instructions on the ESC to set the throttle travel.

Let's review. We have the servos moving in the correct direction and have centered the servos and adjusted the travel to get the recommend travel on all controls. We are ready to fly, right?

Well, maybe not. There are a few more features that you need to be aware of that can help make the model easier and more fun to fly.

## Dual Rates

Let's discuss dual rates. This program allows a pilot to adjust the total travel of a specific control surface with the flip of a switch. A good example of this is on the elevator. Most aircraft instructions will come with travel recommendations for both high and low rates. Previously we set up the high-rate travel. Now, you can adjust low rates.

Referring to the radio manual, select the dual-rate program and choose elevator. Find the switch that controls the elevator dual rates. When the switch is flipped up toward the top or back of the transmitter (depending if it is mounted to the front or top of the transmitter), that is usually the high-rate position. You won't need to make any adjustment for this switch position.

Now flip the switch down or back toward yourself. That will be the low-rate position. Referring to the radio manual, reduce the 100% setting to roughly 70%, or whatever measurement for the control travel at low rates. Adjust the percentage until you achieve the desired amount of travel.

Now, if you hold full up on the elevator stick and flip the switch back and forth, you will see the travel of the elevator change. This allows you to select more or less throw while flying in order to complete a specific maneuver. In the case of elevator, it usually takes more elevator to perform snap rolls or spins that you would want to use in normal flight, so you take off and land and do most of your flying at low rates.

When you want to perform a spin or snap, flip the switch and you have the control you need to do the maneuver. Afterward, switch back to continue flying. Very handy indeed! Go through the rest of the channels and set them up as well. Dual-rate rudder can be helpful to keep you from oversteering on takeoff by switching to low rates when you start the takeoff roll.

## Exponential

Exponential is something that I think most newcomers don't understand. Exponential changes the response of the servo from linear (proportionally following the exact motion of the stick), to a nonlinear response.

Taking elevator and aileron control as examples, most aircraft are sensitive around the neutral point, so only a small amount of control movement is needed to make minor corrections in flight. This is where typical use of exponential comes in. Adding some exponential to the control will make the servo move less when the stick is moved around the neutral point and more when the stick is moved near the end of its travel.

Depending upon the radio system and how it is set up, you can select exponential as part of the dual rate program, so that you can have different amounts of exponential with different amounts of travel as selected by the dual-rate switch position. Again using elevator as the example, enter the radio program for exponential and select elevator. By flipping the dual-rate elevator switch, you can determine where you need to make the change in the exponential program.

At high rates, you will normally want a higher amount of exponential—40% to 70%. Check your manual for recommended amounts. At low-rate elevator, you will normally set a lower amount, maybe 20% to 50%. With these values entered, slowly move the elevator stick from neutral to full up.

You will notice that the control surface moves very little around neutral, but then moves much farther as you get to full stick deflection. Again, do the same for all of the other controls. Sometimes exponential can help with glow and gas engines, because most have almost no power increase from 70% to full throttle. Adding exponential will give a more linear engine response to your throttle stick.

In some instances, you might find that your setting actually results in making the travel around neutral greater and the travel at the end smaller. In this case, you will need to go the reverse direction (negative number) on your exponential input. That is, instead of 40%, make it -40% on the screen. This information is usually in your radio manual, so check that before you start making changes.

Using exponential on ailerons and elevator are a must for me! It makes all of my models—from trainers to jets to 3-D machines—easy to fly. I can fly lazily around, or switch to high rates and high exponential to hover or perform 3-D maneuvers. With many of my models, I don't even use dual rates, only exponential. Then I don't have to flip switches or remember to flip them when I am flying!

## Mixing

Finally, I'll touch on mixing. Most fliers will not get into mixing at all, but some will find it makes certain models easier to fly. Take a J-3 Cub, for instance. Most will turn better using both rudder and ailerons to bank. The full-scale J-3 Cub definitely requires rudder to turn properly!

Using a mix to allow a small amount of rudder to automatically move whenever you use the ailerons can make flying easier, especially for inexperienced pilots. Simply follow the programming instructions and select aileron as the master channel and rudder as the slave.

Set the mix to 10% or whatever is recommended in the aircraft manual. Make sure that the rudder is moving to the right when you are giving right aileron input! If it is backward, simply reduce the number until it reads -10%.

There is normally a switch that turns this mix on and off, so you can steer normally on the ground, but switch the mix on in flight. In crosswind landings, sometimes it is important to be able to turn the mix off to compensate for wind.

I hope this brief introduction into basic radio programming helps you better understand your radio and how its features can enhance your model flying experience and even aid in quickly setting up a new model!

See you at the field!

—Tony Stillman  
[tonys@modelaircraft.org](mailto:tonys@modelaircraft.org)